



◀ Conductive Plastic Potentiometer ▶

APPLICATION 應用

1. Bushings mount for angle control of the situation requires.
側出端子型，適用於需要角度控制的場合。
2. 360° continuous rotation, the effective angle of 340° (can be customized)
360° 連續旋轉，有效角度340°（可定制）
3. Aluminum shell, sealed, in harsh environments.
鋁合金外殼，全密封，可在惡劣環境下適用。

SPECIFICATIONS 規格

Resistance 電阻阻值	1K, 2K, 5K, 10K
Resistance deviation 阻值偏差	±20%
Independent Linearity 獨立線性	±0.5%
Electrical angle 電氣轉角	340° ±5°
Mechanical angle 機械轉角	360° continuous
Insulation Resistance 絕緣電阻	>500DC. 500V/m
Rated Power 額定功率	0.5W/70°C
Resolution 分辨率	Infinte
Smoothness 平滑性	≤1.5%
Temperature coefficient 溫度係數	±500PPM/°C
Strength 耐壓強度	500V. A. C. /min
Starting torque 啟動力矩	<0.098 N(M)
Temperature range 溫度範圍	-40°C ~ +125°C
Rotary Life 回轉壽命	30×10 ⁶ cycles
Protection class 防護等級	IP50

ORDERING INFORMATION 訂購說明

WDJ22B	Resistance 電阻阻值	Angle 電氣/機械角度	Shaft length 軸柄長度	Shaft type 軸柄形式	Shaft diameter 軸柄直徑	Linearity 線性精度
	1K	340° /360°	20:20mm	S: 	6:ø6mm	Blank: ±0.5%
	2K					0.25: ±0.25%
	5K			F: 		
	10K					